







KEY CASE SEB







Tested and approved by construction according to technical requirements **BSI TL 03409**.


Outside: Body: Single-walled Door: Double-walled Fittings: Protruding 30 mm


Inside:

With inner compartments (only possible with size 0 key bar with 7 hooks) Compartment dimensions: height 70 mm, width 160 mm, depth 95 mm; other dimensions are possible on request

The built-in key compartments are provided with double-bit key locks, each with 8 tumblers. Locks are guaranteed to lock differently among each other.

Hinges: External Door opening angle: 180°







9	LOCKING	Strong central locking mechanism with three-sided locking and mechanical combination lock. An electronic key lock can be used as an alternative to the mechanical combination lock. All locks correspond to the BSI's approved lock list . The lock and bolt works are secured against drilling open by armored plates.
V	PAINTING	Light gray, RAL 7035 (special painting according to RAL colors for an extra charge)
\bigcirc	INSURABLE	Individual agreement

Model	External of Height W		n mm Depth	Number of key compartments	Weight ^(Kg)
Key case, Size 0	293	250	190	1-3*	17
Key case, Size 1	295	420	190	4-6	26
Key case, Size 2	508	420	190	7-12	49
Key case, Size 3	941	420	190	13-24	87

* optionally with 7 hooks



LOCKING OPTIONS

	Standardlocking	Optional locking systems		
Model	Mechanical combination lock	Electronic combination lock SELO B		
SEB, Size 0				
SEB, Size 1				
SEB, Size 2				
SEB, Size 3		•		

AUTHORITIES

As of 12/2020 - decorative material not included in the scope of delivery- Technical changes reserved.

D

Müller Safe GmbH In der Hirtenwiese 6 35745 Herborn, Germany www.mueller-safe.de

