



MÜLLER  
SAFE



HIGH SECURITY SAFES

## HIGH SECURITY SAFE **BM VI**



### SECURITY LEVEL

Class VI according to EN 1143-1  
certified by ECB-S



### FIRERATING

LFS 30 according to EN 15659



### DESIGN

**Body:** Multi-walled  
**Door:** Multi-walled  
**Hinges:** External  
**Door opening angle:** 180°  
**Handle/fitting:** Handle, protruding 60 mm  
**Mounting holes:** 1 fixing hole in the floor (1 repared in the backwall)  
Key strip with 5 hooks for self-assembly is included.  
Prepared for EMA-installation



### LOCKING

2 high security double-bit key locks  
each 2 keys



### PAINTING

Light gray, RAL 7035 and Graphite gray, RAL 7024



### INSURABLE

Individual agreement.



**HIGH SECURITY SAFES**

# HIGH SECURITY SAFE BM VI



BM6-0



BM6-1



BM6-2






BM6-3

Model	External dim. in mm			Internal dim. in mm			Door light		Door 1 / 2-leaf	Volume (Liter)	Weight (Kg)
	Height	Width	Depth	Height	Width	Depth	Height	Width			
BM 6-0	790	660	620	550	410	305	544	386	1-leaf	69	740
BM 6-1	1096	756	620	856	506	305	850	482	1-leaf	132	1090
BM 6-2	1296	756	620	1056	506	305	1050	482	1-leaf	163	1270
BM 6-3	1596	926	660	1356	676	425	1350	652	1-leaf	316	1870

Fittings protrude 30 mm



## VERSCHLUSSOPTIONEN

	Standardlocking	Optional locking systems	
Model	 2 Double-bit key locks	 Double lock* (Mechanical combination lock+key lock)	 Doppelverschluss* (2 Electronic combination locks)
BM 6-0	■	■	■
BM 6-1	■	■	■
BM 6-2	■	■	■
BM 6-3	■	■	■

\*other lock combinations possible

As of 12/2022 - decorative material not included in the scope of delivery- Technical changes reserved.



## HIGH SECURITY SAFES



**Müller Safe GmbH**

In der Hirtenwiese 6

35745 Herborn, Germany

[www.mueller-safe.de](http://www.mueller-safe.de)

