



MÜLLER
SAFE



HIGH SECURITY SAFES

HIGH SECURITY SAFE BM III



Model BM3-1



SECURITY LEVEL

Class III according to EN 1143-1
certified by ECB-S



DESIGN

Body: Multi-walled with special reinforcement
Door: Multi-walled
Hinges: External
Door opening angle: 180°
Handle/fitting: Handle, protruding 60 mm
Mounting holes: 1 fixing hole in the floor (1 repared in the backwall)
Key strip with 5 hooks for self-assembly is included.



LOCKING

High security double-bit key lock
2 keys (135 mm)



PAINTING

Light gray, RAL 7035 and Graphite gray, RAL 7024
(special painting according to RAL colors for an extra charge)



INSURABLE

Individual agreement



HIGH SECURITY SAFES

HIGH SECURITY SAFE BM III






Model	External dim. in mm			Internal dim. in mm			Door light		Number Shelves	Door 1 / 2-leaf	Number Files	Volume (Liter)	Weight (Kg)
	Height	Width	Depth	Height	Width	Depth	Height	Width					
BM3-0	450	450	465	350	340	305	318	334	1	1-leaf	4	36	177
BM3-1	550	550	465	450	440	305	418	434	1	1-leaf	7	60	239
BM3-2	700	550	465	600	440	305	568	434	1	1-leaf	9	81	287
BM3-3	850	550	465	750	440	305	718	434	1	1-leaf	10	101	335
BM3-4	1050	550	465	950	440	305	918	434	2	1-leaf	15	127	401
BM3-5	1200	550	465	1100	440	305	1100	434	2	1-leaf	18	148	450
BM3-6	1350	550	465	1250	440	305	1218	434	2	1-leaf	20	168	501

Fittings protrude 30 mm



LOCKING OPTIONS

	Standardlocking	Optional locking systems	
			
Model	Double-bit key lock	Electronic combination lock	Electronic combination lock*
BM3-0	■	■	□
BM3-1	■	■	■
BM3-2	■	■	■
BM3-3	■	■	■
BM3-4	■	■	■
BM3-5	■	■	■
BM3-6	■	■	■

* with emergency key

As of 12/2020 - decorative material not included in the scope of delivery- Technical changes reserved.



HIGH SECURITY SAFES

Müller Safe GmbH

In der Hirtenwiese 6

35745 Herborn, Germany

www.mueller-safe.de

