



MÜLLER
SAFE



GUN SAFES

GUN SAFE WSLO XL



Model WSLO-10/20



SECURITY LEVEL

Class 0 according to EN 1143-1
certified by ECB-SS



DESIGN

Body: Double-walled
Door: Multi-walled
Hinges: External
Door opening angle: 180°
Handle: Protruding 65 mm
Mounting holes: 1 fixing hole in the floor,
1 in the backwall (not drilled through)



LOCKING

High security double-bit key lock
2 keys (95 mm)



PAINTING

Light gray, RAL 7035 or Graphite gray, RAL 7024
(special paint according to RAL colors for an extra charge)



GUN SAFE WSLO XL



WSLO-6/16

WSLO-7/17

WSLO-8/18

WSLO-9/16

WSLO-10/20

Model	External dim. in mm			Internal dim. in mm			Door light		Number Shelves	Number Gunholder	Weight (Kg)
	Height	Width	Depth	Height	Width	Depth	Height	Width			
WSLO-6/16	1500	550	450	1450	500	340	1388	454	2	16	175
WSLO-7/17	1600	655	500	1550	605	390	1488	559	2+2	17	242
WSLO-8/18	1600	600	500	1550	550	390	1488	504	2	18	220
WSLO-9/16	1600	550	500	1550	500	390	1488	454	2	16	207
WSLO-10/20	1600	655	500	1550	605	390	1488	559	2	20	232

Fittings protrude 65 mm, weapon holder on rails adjustable in height and depth

Model	Gun holder per rail		Hooks	Ramrod holder	Partition wall
	back (55 mm)	front (65mm)			
WSLO-6/16	9	7	7	1	0
WSLO-7/17	7+3	5+2	7	1	1
WSLO-8/18	10	8	8	1	0
WSLO-9/16	9	7	11	1	0
WSLO-10/20	11	9	11	1	0



LOCKING OPTIONS

Model	Standardlocking	Optional locking systems	
	Double-bit key lock	Electronic combination lock	Electronic combination lock*
WSLO-6/16	■	■	■
WSLO-7/17	■	■	■
WSLO-8/18	■	■	■
WSLO-9/16	■	■	■
WSLO-10/20	■	■	■

* with emergency key

As of 12/2020 - decorative material not included in the scope of delivery- Technical changes reserved.



GUN SAFES

Müller Safe GmbH

In der Hirtenwiese 6

35745 Herborn, Germany

www.mueller-safe.de

