



MÜLLER
SAFE



FIREPROOF SAFES FOR DOCUMENTS

FIREPROOF SAFE EM



Model EM 031



SECURITY LEVEL

Housing made of steel
Robust against access



FIRE RATING

NT Fire 017-60 Paper, 1 hour
One hour heat test at up to 1100 ° Celsius according to NT FIRE 017-60 Paper



DESIGN

Body: Double-walled
Door: Double-walled
Hinges: External
Door opening angle: 180°
Handle/fitting: Protruding 65 mm
Mounting hole: 1 fixing hole in the floor



LOCKING

Electronic combination lock with two 6-digit user codes



PAINTING

Gray white, RAL 9002



INSURABLE

Individual agreement



FIREPROOF SAFE EM



EM 015



EM 020



EM 031

Model	External dim. in mm			Internal dim. in mm			Door light		Number Shelves	Door 1 / 2-leaf	Volume (Liter)	Weight (Kg)
	Height	Width	Depth	Height	Width	Depth	Height	Width				
EM 015	296	390	320	215	310	215	215	310	1	1-leaf	14	27
EM 020	344	480	388	220	355	260	220	355	1	1-leaf	20	49
EM 031*	520	410	445	415	305	320	415	305	1	1-leaf	40	60

Fittings protrude 35 mm * Drawer H = 50 mm



LOCKING OPTIONS

Standardlocking



Electronic combination lock

Model	Electronic combination lock
EM 015	■
EM 020	■
EM 031	■

As of 01/2022 - decorative material not included in the scope of delivery- Technical changes reserved.



FIREPROOF SAFES FOR DOCUMENTS

Müller Safe GmbH

In der Hirtenwiese 6

35745 Herborn, Germany

www.mueller-safe.de

