





FIREPROOF SAFES FOR DATA CARRIES



FIREPROOF SAFE PG















SECURITY LEVEL

Class I according to EN 1143-1

certified by VdS

6

FIRE RATING S 60 DIS according to EN 1047-1

DESIGN Body: Multi-walled

Door: Multi-walled Hinges: External

Door opening angle: 180°

Handle/fitting: Protruding 65 mm

Mounting holes: 2 fixing holes in the floor

LOCKING

High security double-bit key lock

2 keys (120 mm)

8

PAINTING Light gray, RAL 7035

(special painting according to RAL colors for an extra charge)

V

INSURABLE Individual agreement



FIREPROOF SAFE PG















Model	Extern Height	al dim. Width	in mm Depth	Intern Height	al dim. Width	in mm Depth	Door Height	light Width	Number Shelves	Door 1 / 2-leaf	Volume (Liter)	Weight (Kg)
PG 636	635	563	630	400	368	397	400	368	1	1-leaf	58	198
PG 637	635	563	755	400	368	522	400	368	1	1-leaf	76	223

Fittings protrude 65 mm

LOCKING OPTIONS

Model	Standardlocking	Optional locking systems				
		Electronic	Electronic			
	Double-bit key lock	combination lock	combination lock*			
PG 636	•	•				
PG 637	•	•				

^{*} with emergency key

ACCESSORIES FOR EXTRA CHARGE Left door hinge Additional shelf Shelf for Special fixing kit for concrete floor Model Suspension file on telescopic rails hanging files PG 636 PG 637

 $As of 01/2022 - decorative \ material \ not \ included \ in \ the \ scope \ of \ delivery-\ Technical \ changes \ reserved.$



