



**MÜLLER
SAFE**



DEPOSIT/BANK EQUIPMENT

DEPOSIT SAFE MD I



SECURITY LEVEL

Class D-I according to EN 1143-2
certified by ECB•S



DESIGN

Body: Multi-walled
Door: Multi-walled
Hinges: External
Door opening angle: 180°
Handle/fitting: Protruding 35 mm
Mounting holes: 4 fixing holes in the floor, 1 in the backwall*
(*not drilled through)



LOCKING

High security double-bit key lock
2 keys (95 mm)



PAINTING

Light gray, RAL 7035
(special painting according to RAL colors for an extra charge)



INSURABLE

Individual agreement



DEPOSIT SAFE MD I



MD I-93V

MD I-128V

MD I-93R

MD I-128R

MD I-93

MD I-128

Model	External dim. in mm			Internal dim. in mm			Door light		Drawer	Weight (kg)
	Height	Width	Depth	Height	Width	Depth	Height	Width		
MD I-93V	930	570	510	265	480	390	508	474	front	165
MD I-128V	1280	570	510	615	480	390	858	474	front	205
MD I-93R	930	570	510	265	480	390	508	474	on the back	165
MD I-128R	1280	570	510	615	480	390	858	474	on the back	205
MD I-93	930	570	510+270	265	480	390	508	474	protruding 270mm on the back	180
MD I-128	1280	570	510+270	615	480	390	858	474	protruding 270mm on the back	225

Fittings protrude 35 mm



LOCKING OPTIONS

	Standardlocking	Optional locking systems		
Model	Double-bit key lock	Mechanical combination lock	Electronic combination lock	Electronic combination lock*
MD I-93V	■	■	■	■
MD I-128V	■	■	■	■
MD I-93R	■	■	■	■
MD I-128R	■	■	■	■
MD I-93	■	■	■	■
MD I-128	■	■	■	■

*with emergency key



ACCESSORIES FOR EXTRA CHARGE

Model	Left door hinge	Shelf	Additional fixing hole for designated position Ø = 16 mm	Special fixing kit for concrete floor
MD I-93V	■	■	■	■
MD I-128V	■	■	■	■
MD I-93R	■	■	■	■
MD I-128R	■	■	■	■
MD I-93	■	■	■	■
MD I-128	■	■	■	■

As of 01/2022 - decorative material not included in the scope of delivery - Technical changes reserved.



DEPOSIT/BANK EQUIPMENT

Müller Safe GmbH

In der Hirtenwiese 6

35745 Herborn, Germany

www.mueller-safe.de

