



MÜLLER
SAFE



HIGH SECURITY SAFES



**MÜLLER
SAFE**

HIGH SECURITY SAFE **BM VI**



SECURITY LEVEL

Class VI according to EN 1143-1
certified by ECB-S



FIRERATING

LFS 30 according to EN 15659



DESIGN

Body: Multi-walled
Door: Multi-walled
Hinges: External
Door opening angle: 180°
Handle/fitting: Handle, protruding 60 mm
Mounting holes: 1 fixing hole in the floor (1 repaired in the backwall)
Key strip with 5 hooks for self-assembly is included.
Prepared for EMA-installation



LOCKING

2 high security double-bit key locks
each 2 keys



PAINTING

Light gray, RAL 7035 and Graphite gray, RAL 7024



INSURABLE

Individual agreement.



HIGH SECURITY SAFES

HIGH SECURITY SAFE BM VI



Model	External dim. in mm			Internal dim. in mm			Door light		Door 1 / 2-leaf	Volume (Liter)	Weight (Kg)
	Height	Width	Depth	Height	Width	Depth	Height	Width			
BM 6-0	790	750	620	550	500	305	544	475	1-leaf	84	810
BM 6-1	996	750	620	756	500	305	750	475	1-leaf	127	990
BM 6-2	1296	750	620	1056	500	305	1050	475	1-leaf	162	1260
BM 6-3	1590	850	740	1350	600	425	1344	575	1-leaf	344	1860

Fittings protrude 30 mm



VERSCHLUSSOPTIONEN

Model	Standardlocking	Optional locking systems	
	2 Double-bit key locks	Double lock* (Mechanical combination lock+key lock)	Doppelverschluss* (2 Electronic combination locks)
BM 6-0	■	■	■
BM 6-1	■	■	■
BM 6-2	■	■	■
BM 6-3	■	■	■

*other lock combinations possible

As of 12/2022 - decorative material not included in the scope of delivery- Technical changes reserved.



HIGH SECURITY SAFES

Müller Safe GmbH

In der Hirtenwiese 6

35745 Herborn, Germany

www.mueller-safe.de

