





DEPOSIT/BANK EQUIPMENT



DEPOSIT SAFE GT EW















SECURITY LEVEL

Security rating B to VDMA 24992 (Conditions May '95)



DESIGN

Body: Double-walled Door: Double-walled Hinges: Internal

Door opening angle: 90°

Mounting holes: 1 fixing hole in the floor

Money bombs are placed in the pulled-out drawer and fall into the interior of the safe. The drawer on telescopic runners allows easy use. If the safe is located in an adjoining room and the deposit (drawer) is to be made through the masonry / wall, the wall thickness may not exceed 150 mm.



LOCKING

High security double-bit key lock 2 keys (95 mm)



PAINTING

Light gray, RAL 7035



INSURABLE

(special painting according to RAL colors for an extra charge)

Individual agreement

DEPOSIT SAFE GT EW













GT EW

GT EW with insert drawer

Model	Extern Height	al dim. Width	in mm Depth	Intern Height	al dim. Width	in mm Depth	Number Shelves	Number Files	Volume (Liter)	Weight (Kg)
GT EW	800	600	500	560	460	360	1	5	96	300
Insert drawer		eccording espective		105	220	170				22

LOCKING OPTIONS

	Standardlocking	Optional locking systems					
Model	Double-bit key lock	Mechanical combination lock	Electronic combination lock	Electronic combination lock*	Double lock** (2 Double-bit key locks)		
GT EW			•	•			

 $[\]ensuremath{^{\star}}$ with emergany key $\ensuremath{^{\star\star}}$ other lock combinations possible



Model	Left door hinge	Additional fixing hole for designated position	Special fixing kit for concrete floor	
GT EW	•	•	•	

 $As of 01/2022 - decorative \ material \ not \ included \ in \ the \ scope \ of \ delivery-\ Technical \ changes \ reserved.$



