



MÜLLER
SAFE



GUN SAFES

GUN SAFE WSL1



Modell WSL1-4/7



SECURITY LEVEL

Class I according to EN 1143-1
certified by ECB•S



DESIGN

Body: Double-walled
Door: Multi-walled
Hinges: External
Door opening angle: 180°
Handle: Protruding 30 mm
Mounting holes: 1 fixing hole in the floor,
1 in the backwall (not drilled through)



LOCKING

High security double-bit key lock
2 keys (95 mm)



PAINTING

Light gray, RAL 7035 or Graphite gray, RAL 7024
(special paint according to RAL colors for an extra charge)



GUN SAFE WSL1



Model	External dim. in mm			Internal dim. in mm			Door light		Number Shelves	Number Gunholder	Weight (Kg)
	Height	Width	Depth	Height	Width	Depth	Height	Width			
WSL1-1/5	1250	350	350	1200	300	240	1138	254	0	5	109
WSL1-2/7	1250	450	350	1200	400	240	1138	354	0	7	126
WSL1-3/5	1500	350	350	1450	300	240	1388	254	1	5	131
WSL1-4/7	1500	450	350	1450	400	240	1388	354	1	7	150
WSL1-5/9	1500	450	450	1450	400	340	1388	354	1	9	170
WSL1K-1/4	1500	450	450	1450	400	340	1388	354	3	4	172
WSL1K-2/7	1500	550	450	1450	500	340	1388	454	3	7	199

Fittings protrude 30 mm

Model	Gun holder per rail		Number Hooks	Number Ramrod holder	Number Partition wall
	back (55 mm)	front (65mm)			
WSL1K-1/4	4	-	4	1	1
WSL1K-2/7	4	3	7	1	1



LOCKING OPTIONS

Model	Standardlocking	Optional locking systems	
	Double-bit key lock	Electronic combination lock	Electronic combination lock*
WSL1-1/5	■	■	■
WSL1-2/7	■	■	■
WSL1-3/5	■	■	■
WSL1-4/7	■	■	■
WSL1-5/9	■	■	■
WSL1K-1/4	■	■	■
WSL1K-2/7	■	■	■

* with emergency key

As of 01/2022 - decorative material not included in the scope of delivery- Technical changes reserved.



GUN SAFES

Müller Safe GmbH

In der Hirtenwiese 6

35745 Herborn, Germany

www.mueller-safe.de

