



MÜLLER
SAFE



HIGH SECURITY SAFES

HIGH SECURITY SAFE **BM VII**



SECURITY LEVEL

Class VII according to EN 1143-1
certified by ECB-S



FIRERATING

LFS 30 according to EN 15659



DESIGN

Body: Multi-walled
Door: Multi-walled
Hinges: External
Door opening angle: 180°
Handle/fitting: Handle, protruding 60 mm
Mounting holes: 1 fixing hole in the floor (1 repared in the backwall)
Key strip with 5 hooks for self-assembly is included.
Prepared for EMA-installation



LOCKING

2 high security double-bit key locks
each 2 keys



PAINTING

Light gray, RAL 7035 and Graphite gray, RAL 7024



INSURABLE

Individual agreement.



HIGH SECURITY SAFE **BM VII**



BM7-0

BM7-1

BM7-2

BM7-3

BM7-4



BM7-5

BM7-6

BM7-7

Model	External dim. in mm			Internal dim. in mm			Door light		Door 1 / 2-leaf	Volume (Liter)	Weight (Kg)
	Height	Width	Depth	Height	Width	Depth	Height	Width			
BM 7-0	830	790	660	550	500	305	544	475	1-leaf	84	1010
BM 7-1	1036	790	660	756	500	305	750	475	1-leaf	115	1230
BM 7-2	1336	790	660	1056	500	305	1050	475	1-leaf	161	1540
BM 7-3	1630	890	780	1350	600	425	1344	575	1-leaf	344	2260
BM 7-4	2080	990	780	1800	700	425	1794	675	1-leaf	536	3060
BM 7-5	1180	790	855	900	500	500	894	475	1-leaf	225	1660
BM 7-6	1480	790	855	1200	500	500	1200	475	1-leaf	300	2020
BM 7-7	1780	790	855	1500	500	500	1494	475	1-leaf	375	2380

Fittings protrude 115 mm



VERSCHLUSSOPTIONEN

Model	Standardlocking	Optional locking systems	
	2 Double-bit key locks	Double lock* (Mechanical combination lock+key lock)	Doppelverschluss* (2 Electronic combination locks**)
BM 7-0	■	■	■
BM 7-1	■	■	■
BM 7-2	■	■	■
BM 7-3	■	■	■
BM 7-4	■	■	■
BM 7-5	■	■	■
BM 7-6	■	■	■
BM 7-7	■	■	■

*other lock combinations possible ** with emergency key

As of 12/2022 - decorative material not included in the scope of delivery- Technical changes reserved.



HIGH SECURITY SAFES

Müller Safe GmbH

In der Hirtenwiese 6

35745 Herborn, Germany

www.mueller-safe.de

