



MÜLLER
SAFE



HIGH SECURITY SAFES

HIGH SECURITY SAFE **BM VI**



SECURITY LEVEL

Class VI according to EN 1143-1
certified by ECB-S



FIRERATING

LFS 30 according to EN 15659



DESIGN

Body: Multi-walled
Door: Multi-walled
Hinges: External
Door opening angle: 180°
Handle/fitting: Handle, protruding 60 mm
Mounting holes: 1 fixing hole in the floor (1 repared in the backwall)
Key strip with 5 hooks for self-assembly is included.
Prepared for EMA-installation



LOCKING

2 high security double-bit key locks
each 2 keys



PAINTING

Light gray, RAL 7035 and Graphite gray, RAL 7024



INSURABLE

Individual agreement.



HIGH SECURITY SAFE **BM VI**



BM6-0

BM6-1

BM6-2

BM6-3

Model	External dim. in mm			Internal dim. in mm			Door light		Door 1 / 2-leaf	Volume (Liter)	Weight (Kg)
	Height	Width	Depth	Height	Width	Depth	Height	Width			
BM 6-0	790	750	620	550	500	305	544	475	1-leaf	84	810
BM 6-1	996	750	620	756	500	305	750	475	1-leaf	127	990
BM 6-2	1296	750	620	1056	500	305	1050	475	1-leaf	162	1260
BM 6-3	1590	850	740	1350	600	425	1344	575	1-leaf	344	1860

Fittings protrude 115 mm



VERSCHLUSSOPTIONEN

Model	Standardlocking	Optional locking systems	
	2 Double-bit key locks	Double lock* (Mechanical combination lock+key lock)	Doppelverschluss* (2 Electronic combination locks)
BM 6-0	■	■	■
BM 6-1	■	■	■
BM 6-2	■	■	■
BM 6-3	■	■	■

*other lock combinations possible

As of 12/2022 - decorative material not included in the scope of delivery- Technical changes reserved.



HIGH SECURITY SAFES

Müller Safe GmbH

In der Hirtenwiese 6

35745 Herborn, Germany

www.mueller-safe.de

