



MÜLLER  
SAFE



STRONGROOM DOORS

## STRONGROOM DOOR ATi I



Model ATiI-20E



### SECURITY LEVEL

Class I according to EN 1143-1  
certified by ECB-S and VdS



### DESIGN

**Door:** Multi-walled  
**Hinges:** External  
**Door opening angle:** 180°  
**Handle/fitting:** Protruding 65 mm  
**Door opening inwards**



### LOCKING

High security double-bit key lock  
2 keys (150 mm)



### PAINTING

Light gray, RAL 7035  
(special paint according to RAL colors for an extra charge)



### INSURABLE

Individual agreement



# STRONGROOM DOOR ATi I



Model	External dim. in mm		Wall opening in mm		Door light in mm		Weight (Kg)
	Height	Width	Height	Width	Height	Width	
ATi I-18B	1790	860	1800	880	1650	670	210
ATi I-20B	1990	960	2000	980	1850	770	230
ATi I-22B	2190	960	2200	980	2050	770	240
ATi I-18E	1820	920	1800	880	1650	670	210
ATi I-20E	2020	1020	2000	980	1850	770	230
ATi I-22E	2220	1020	2200	980	2050	770	240

B = block frame, E = corner frame

Fittings protrude 65 mm

The corner frame is standard on all AT (i) doors.

The frame depth (= wall thickness) is 240 mm as standard. Special dimensions are possible. For wall thicknesses less than 180 mm, fastening by screwing through the frame bushes is not recommended.



## LOCKING OPTIONS

Model	Standardlocking		Optional locking systems		
	Double-bit key lock	Mechanical combination lock	Electronic combination lock	Electronic combination lock*	Double lock** (2 Double-bit key locks)
ATi I-18B	■	■	■	■	■
ATi I-20B	■	■	■	■	■
ATi I-22B	■	■	■	■	■
ATi I-18E	■	■	■	■	■
ATi I-20E	■	■	■	■	■
ATi I-22E	■	■	■	■	■

\* with emergency key \*\* other lock combinations possible



## ACCESSORIES FOR EXTRA CHARGE

Model	Day-door	Electric emergency opening from the inside with ELO Basic (only possible if ELO Basic equipped)	Inner blockage system	Left door hinge
ATi I-18B	■	■	■	■
ATi I-20B	■	■	■	■
ATi I-22B	■	■	■	■
ATi I-18E	■	■	■	■
ATi I-20E	■	■	■	■
ATi I-22E	■	■	■	■

As of 01/2022 - decorative material not included in the scope of delivery- Technical changes reserved.



STRONGROOM DOORS



**Müller Safe GmbH**

In der Hirtenwiese 6

35745 Herborn, Germany

[www.mueller-safe.de](http://www.mueller-safe.de)

